

2013 PLS-CADD Advanced Training and User Group

Leg & Guy Extension XML


by

Jesse Kohler, P.E.

Power Line Systems, Inc.

Leg & Guy Extension Report

- Gives information about structure's joints & additional distances required to intersect TIN surface



Report Options

Leg Extensions and Guy Lengths

Note: This feature will not work unless you have a TIN model and structure files saved by our structure programs.

Structure Range
Start: Substation
End: 10

Output Options
 Include guys
 Include legs/poles

Minimum reveal (ft): -3.28
Maximum reveal (ft): 3.28
Minimum slope intersect length (length of member + required extension) (ft): -3.28
Maximum slope intersect length (length of member + required extension) (ft): 3.28
Maximum allowable difference between slope intersect length and current member length (ft): 328.08

OK Cancel

Locations with less reveal than this marked NG and colored red

Locations with more reveal than this marked NG and colored red

Locations requiring a leg or member size shorter than this marked NG and colored red

Locations requiring a leg or member size longer than this marked NG and colored red

Locations requiring a change in leg or member size greater than this marked NG and colored red

Information in Report

- Important information like member xyz coordinates and length required to intersect TIN surface allow calculations using XML to automate determination of appropriate body/leg tower extensions or pole height/embedments to fit TIN surface.

Leg and Guy Extension Report

In the report below the program has identified structure members that are connected to fixed joints. The program has projected the X and Y coordinates of these joints onto the TIN model to determine the ground elevation below these joints. The program has also calculated the point of intersection of a line passing through these structure members and the TIN model. Values of -9999 indicate there is no valid TIN model at the specified point.

Warning: The results below are based on the coordinates of fixed joints in the structure model. These results may need to be adjusted if the structures were modeled with a fixity point other than ground.

Structure Number	Member Label or Type	From Joint	To Joint	Member Length (ft)	Member Top Z (ft)	Member Bottom X (ft)	Member Bottom Y (ft)	Member Bottom Z (ft)	TIN Z at Member Bot. (ft)	Reveal at Member XY (ft)	Slope Intersect X (ft)	Slope Intersect Y (ft)	Slope Intersect Z (ft)	Intersect Required (ft)	Intersect Required (ft)	OK NG
3	66P	100S	120S	30.668	1460.28	2447.60	-0.00	1430.28	1430.52	-0.24	2447.66	-0.00	1430.52	-0.24	30.42	NG
	66X	100X	120X	30.668	1460.28	2467.05	19.45	1430.28	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	66XY	100XY	120XY	30.668	1460.28	2486.50	0.00	1430.28	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	66Y	100Y	120Y	30.668	1460.28	2467.05	-19.45	1430.28	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
4	70P	100S	120S	22.342	1430.47	2454.93	-860.70	1408.47	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	70X	100X	120X	22.342	1430.47	2479.18	-860.70	1408.47	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	70XY	100XY	120XY	22.342	1430.47	2479.18	-884.96	1408.47	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	70Y	100Y	120Y	22.342	1430.47	2454.93	-884.96	1408.47	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
5	70P	100S	120S	22.342	1418.06	2454.93	-1609.56	1396.06	1390.47	5.59	2454.19	-1608.82	1390.14	6.01	28.36	NG
	70X	100X	120X	22.342	1418.06	2479.18	-1609.56	1396.06	1405.00	-8.94	2478.16	-1610.59	1404.24	-8.30	14.04	NG
	70XY	100XY	120XY	22.342	1418.06	2479.18	-1633.82	1396.06	1404.68	-8.62	2478.19	-1632.83	1403.98	-8.04	14.30	NG
	70Y	100Y	120Y	22.342	1418.06	2454.93	-1633.82	1396.06	1389.03	7.03	2453.98	-1634.76	1388.49	7.69	30.03	NG
6	66XY	100XY	120XY	10.223	1433.95	2451.86	-2388.00	1423.95	1423.98	-0.03	2451.86	-2388.00	1423.98	-0.03	10.19	NG
	66Y	100Y	120Y	10.223	1433.95	2467.06	-2372.80	1423.95	1423.15	0.79	2467.06	-2372.62	1423.15	0.82	11.04	NG
	66P	100S	120S	10.223	1433.95	2482.26	-2388.00	1423.95	1421.93	2.02	2482.71	-2388.00	1421.87	2.13	12.35	NG
	66X	100X	120X	10.223	1433.95	2467.06	-2403.20	1423.95	1423.34	0.61	2467.06	-2403.34	1423.33	0.63	10.86	NG
9	P	P:t	P:g	131.916	1423.22	5639.76	-2388.00	1291.31	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	gl	MR:C	\$Gnd1	152.919	1399.44	5639.76	-2512.06	1291.31	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
10	66P	100S	120S	21.978	1311.52	6709.15	-2401.75	1290.03	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	66X	100X	120X	21.978	1311.52	6709.15	-2374.25	1290.03	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	66XY	100XY	120XY	21.978	1311.52	6736.65	-2374.25	1290.03	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??
	66Y	100Y	120Y	21.978	1311.52	6736.65	-2401.75	1290.03	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	-9999.00	??

Export to XML





- Right clicking inside the report allows the export of XML.
- Almost all reports in PLS software support XML export.

The screenshot shows a software interface with a data table and a context menu. The table has columns for 'Member Bottom Y (ft)' and 'Member Bottom (ft)'. The context menu is open, showing options like 'Table View', 'Goto', 'XML Export', and 'Print...'. The 'XML Export' option is selected, and a sub-menu is visible with 'Export All', 'Leg and Guy Extension Report', and 'Guy Length Report'. The 'Leg and Guy Extension Report' option is highlighted with a red box.

Member Bottom Y (ft)	Member Bottom (ft)	Intersect Addl. Required (ft)	Intersect Total Required (ft)	OK or NG
-0.00	1430.2	-0.24	30.42	NG
19.45	1430.2	-9999.00	-9999.00	?? Can't find ir
0.00	1430.2	-9999.00	-9999.00	?? Can't find ir
-19.45	1430.2	-9999.00	-9999.00	?? Can't find ir
-860.70	1408.4	-9999.00	-9999.00	?? Can't find ir
-860.70	1408.4	-9999.00	-9999.00	?? Can't find ir
-884.96	1408.4	-9999.00	-9999.00	?? Can't find ir
-884.96	1408.4	-9999.00	-9999.00	?? Can't find ir
-1609.56	1396.0	-8.30	14.04	NG
-1609.56	1396.0	-8.04	14.30	NG
-1633.82	1396.0	7.69	30.03	NG
-1633.82	1396.0	-0.03	10.19	NG
-2388.00	1423.9	0.82	11.04	NG
-2372.80	1423.9	2.13	12.35	NG
-2388.00	1423.9	0.63	10.86	NG
-2403.20	1423.9	-9999.00	-9999.00	?? Can't find ir
-2388.00	1291.3	-9999.00	-9999.00	?? Can't find ir
-2512.06	1291.3	-9999.00	-9999.00	?? Can't find ir
-2401.75	1290.0	-9999.00	-9999.00	?? Can't find ir
-2374.25	1290.0	-9999.00	-9999.00	?? Can't find ir
-2374.25	1290.0	-9999.00	-9999.00	?? Can't find ir
-2401.75	1290.0	-9999.00	-9999.00	?? Can't find ir

XML into MS Excel Options

- Source Task Pane (drag/drop only items you want and refresh data to pull in)
- Table (all available data in XML dumped into table)




Macros and VBA to Automate

- Simple macros or more advanced VBA routines can be implemented to automate calculations and quickly perform tasks like finding leg/body extensions or pole heights/embedments to fit TIN surface

Leg & Body Ext Finder.xlsx - Microsoft Excel

Structure Number	Tower Leg	Option 1			Option 4		
		Leg Extension	Body Extension	Reveal	Leg Extension	Body Extension	Reveal
5	66P	12.5	None	2.4	None	30	-15.1
	66X	No TIN	No TIN	No TIN	No TIN	No TIN	No TIN
	66Y	No TIN	No TIN	No TIN	No TIN	No TIN	No TIN
	66XY	No TIN	No TIN	No TIN	No TIN	No TIN	No TIN
9	70P	None	None	1.7	None	30	-28.3
	70X	None	None	-12.0	None	30	-42.0
	70Y	2.5	None	0.8	None	30	-26.7
	70XY	None	None	-11.7	None	30	-41.7
	70P	27.5	None	2.5	None	30	0.0
	70X	20	None	1.6	None	30	-8.4
				1.0	None	30	-1.5
				2.6	None	30	-9.9
				6.9	12.5	30	1.9
				25.2	30	30	2.7
				3.2	10	30	0.7
				9.9	15	30	2.4



Power Line Systems

IT'S ALL ABOUT YOUR POWER LINES

Advanced Sag & Tension

IEC

FAC 008/009

NESC

Materials Management

LiDAR Modeling

PLS-CADD[®]

CSA

Distribution

Structural Analysis

Pole Analysis

CENELEC

NERC Ratings

Transmission

Line

Optimization

Project Estimating

Questions?

FAC 003

ASCE

Joint Use

PLS-POLE

Vegetation Management

POWER LINE[®]

1000+ Users in 100+ Countries

Storm Hardening

S Y S T E M S · I N C ·

IEEE

Line Ratings

Madison, Wisconsin 53705, USA

TOWER

Drafting

Phone: 608-238-2171 Fax: 608-238-9241

info@powline.com www.powline.com

IT'S THE SOLUTION